




WEISSENFELS




Chain Sling Components – Alloy Grade 80 and Grade 100

Weisslocks (G80 & G100)




Stock No G80	Stock No G100	Chain Size	WLL Lbs* Grade 80	WLL Lbs* Grade 100	Dimensions in Inches							WT. EA. LBS
					A	B	C	D	E	F	PxL	
WA58	WA58-10	1/4(6mm)	2,460	3,050	0.71	1.77	0.71	0.31	0.30	0.55	.19x1.52	0.15
WA60	WA60-10	9/32	3,500	4,300	0.75	2.01	0.79	0.39	0.35	0.63	.24x1.83	0.22
WA59	WA59-10	5/16	4,500	5,700	0.91	2.44	0.98	0.45	0.39	0.71	.25x2.09	0.55
WA61	WA61-10	3/8	7,100	8,800	1.06	2.83	1.18	0.50	0.5	0.91	.31x2.5	0.77
WA62	WA62-10	1/2	12,000	15,000	1.34	3.46	1.42	0.75	0.66	1.06	.39x3.11	1.50
WA63		5/8	18,100	22,600	1.54	4.06	1.57	0.83	0.83	1.30	.55x4.17	3.25
WA64		3/4	28,300		1.85	4.52	1.76	1.16	0.96	1.64	.63x4.82	5.29
WA65		7/8	34,200		2.17	5.24	3.11	1.06	1.06	1.90	.63x5.28	5.95
WA66		1	47,700		2.60	6.46	2.68	1.26	1.18	2.40	.71x6.26	11.22
WA67		1-1/4	72,300		3.39	7.64	3.15	1.57	1.26	3.15	.98x7.68	18.71

Clevis Sling Hook (G80 & G100)



Stock No G80	Stock No G100	Chain Size	WLL Lbs* Grade 80	WLL Lbs* Grade 100	Dimensions in Inches										WT. EA. LBS
					A	A1	B	C	G	H	R	X	Y	PxL	
WA79	WA79-10	1/4(6mm)	2,460	3,050	1.02	0.75	0.28	0.31	0.59	0.79	2.72	2.60	4.02	.29x.65	0.53
WA80	WA80-7-10	9/32	3,500	4,300	1.34	1.02	0.37	0.39	0.75	1.10	3.74	3.54	5.51	.35x.91	1.17
WA80	WA80-8-10	5/16	4,500	5,700	1.34	1.02	0.37	0.39	0.75	1.10	3.74	3.54	5.51	.39x.91	1.17
WA81	WA81-10	3/8	7,100	8,800	1.57	1.22	0.47	0.53	0.98	1.30	4.33	4.25	6.50	.39x.91	2.09
WA82	WA82-10	1/2	12,000	15,000	2.01	1.57	0.59	0.67	1.18	1.57	5.35	5.16	8.03	.49x1.16	3.68
WA83	WA83-10	5/8	18,100	22,600	2.20	1.77	0.71	0.87	1.46	1.89	6.10	6.02	9.33	.78x2.05	5.95
WA84		3/4	28,300		2.40	2.05	0.91	1.02	1.81	2.05	7.20	6.97	10.9	.94x2.87	11.88
WA85		7/8	34,200		2.83	2.60	0.96	1.14	1.97		8.39	7.73	12.6	1.06x2.80	19.37

Eye Sling Hook (G80 & G100)



Stock No G80	Stock No G100	Chain Size	WLL Lbs* Grade 80	WLL Lbs* Grade 100	Dimensions in Inches							WT. EA. LBS
					A	A1	D	G	H	O	R	
WA.29	WA29-10	1/4(6mm)	2,460	3,050	1.02	0.75	0.39	0.63	0.79	0.81	3.19	0.53
WA.30	WA30-10	9/32-5/16	4,500	5,700	1.30	1.02	0.43	0.75	1.14	0.98	3.98	1.10
WA.31	WA31-10	3/8	7,100	8,800	1.57	1.22	0.63	1.02	1.30	1.34	5.16	1.98
WA.32	WA32-10	1/2	12,000	15,000	2.01	1.57	0.75	1.30	1.65	1.69	6.26	3.53
WA.33	WA33-10	5/8	18,100	22,600	2.20	1.77	0.96	1.57	1.97	1.97	7.20	6.50
WA.34		3/4	28,300		2.44	2.09	1.06	1.89	2.17	2.17	8.07	10.36
WA.35		7/8	34,200		2.99	2.44	1.14	1.97	2.44	2.36	8.86	16.09
WA.36		1	47,700		3.15	2.87	1.38	2.36	2.95	2.76	10.12	21.60
WA.37		1-1/4	72,300		4.00	3.43	1.54	2.80	3.50	2.60	11.77	36.16